

Hydraulic 250 kN 2-Drum Anchor / Mooring Winch

TTR Code no.: 15.085

Specifications

Type	: 2-Drum anchor / mooring winch
Line-pull	: 250 kN – 1 st layer @ 200 Bar 150 kN – full drum @ 200 Bar
Line-speed	: 11 mtr/min. – 1 st layer @ 200 ltr/min. 15.5 mtr/min. – full drum @ 200 ltr/min.
Brake holding power	: Min. 375 kN

Drum size each drum

Drum dia	: 700mm
Drum length	: 680mm
Flange dia	: 1320mm
Wire capacity	: 580 mtr Ø32mm 10 layers

Drive

Hydraulic motor	: Staffa
Type	: HMB080S
Displacement	: 1344 cm ³ /rev
Gear ratio	: 1:28

Dimensions

Dimensions o.a.	: 3270 x 20710 x 1680mm (L x W x H)
Base frame	: 3270 x 2070 mm (L x W)
Weight	: Appr. 10 tn excl. steel wire

General

Hand operated clutch and handbrake on each drum

Tenwolde Transport
en Repair B.V.

P.O. Box 5023
3274 ZJ Heineoord
the Netherlands

Tel: +31(0)186-603333
Fax: +31(0)186-603619
info@tenwolde.com

Visiting address:
Boonsweg 19
3274 LH Heineoord
the Netherlands

