

Hydraulic 2 Drum Anchor/ Mooring Winch (3 pcs.)

TTR Code no.: 15.059

Specifications

Type:	AHW 2 SBS
NO.:	WO. 3946 + 3963
Line pull 1 st layer:	40 tn - 289 bar 25 tn – full drum
Line speed 1 st layer:	0 – 20 m/min - 345 ltr/min) 0 – 28 m/min – full drum

Drum size

Drum diameter:	1067 mm
Drum length:	610 mm
Flange diameter:	1840 mm
Wire capacity:	505 mtr steel wire Ø 44 mm (9 layers)

Drive

Hydraulic motor:	Mannesmann Rexroth A2F500 Gear reduction : 117,5
------------------	---

Dimensions

Dimensions o.a.:	5000 x 2800 x 2330 mm (L x W x H)
Dim. base frame:	5000 x 2618 mm (LxW)
Weight:	Approx. 15.500 kg (excl. steel wire)

General

Pneumatic operated band brake on drums, Pawl and Clutches
hand operated hydraulic steering valve on winch

Tenwolde Transport
en Repair B.V.

P.O. Box 5023
3274 ZJ Heinoord
the Netherlands

Tel: +31(0)186-603333
Fax: +31(0)186-603619
info@tenwolde.com

Visiting address:
Boonsweg 19
3274 LH Heinoord
the Netherlands

